



SPECIFICATIONS

Max. Wheel diameter	25mm
Collet chuck	6.35mm (standard)
Input power	520W
No load speed	29,000 (min-1)
Weight	1.7kg
Length	359mm
Standard accessories	Side handle and wrench

Note: Specifications may change without notice

KEY SELLING POINTS

- ❖ **520W motor** for heavy duty performance
- ❖ **Lockable slide switch**
- ❖ **Overall length** is 359mm allowing increased flexibility in applications
- ❖ **High no load speed:** 29,000/min for better finishing applications
- ❖ **All ball bearing construction** for extended tool life
- ❖ **Extended front housing** allows easy access to recessed work pieces
- ❖ **Lightweight** at 1.7Kg for reduced user fatigue

Product Information

GP3V – 25mm Die Grinder



SPECIFICATIONS

Max. Wheel diameter	25mm
Collet chuck	6.35mm (standard)
Input power	760W
No load speed	7000 - 29,000 (min-1)
Weight	1.8kg
Length	406mm
Standard accessories	Side handle and wrench

Note: Specifications may change without notice

KEY SELLING POINTS

- ❖ **Powerful 760W motor** for heavy duty performance
- ❖ **Slide top switch**
- ❖ **Overall length** of 406mm allowing increased flexibility in applications
- ❖ **High no load speed** at 29,000/min for better finishing applications
- ❖ **All ball bearing construction** for extended tool life
- ❖ **Extended front housing** allows easy access to recessed work pieces
- ❖ **Lightweight** at 1.8Kg for reduced user fatigue
- ❖ **Features constant speed control, soft start speed control and variable speed control** for improved control and safety

Product Information
GP5V – 50mm Die Grinder



SPECIFICATIONS

Max. Wheel diameter	50mm
Collet chuck	6.35mm (standard)
Input power	760W
No load speed	2000 - 8,300 (min-1)
Weight	1.9kg
Length	406mm
Standard accessories	Side handle and 2 x wrench

Note: Specifications may change without notice

KEY SELLING POINTS

- ❖ **Powerful 760W motor** for heavy duty performance
- ❖ **Slide top switch**
- ❖ **Overall length** of 406mm allowing increased flexibility in applications
- ❖ **High no load speed** at 8,300 (min-1) for better finishing applications
- ❖ **All ball bearing construction** for extended tool life
- ❖ **Extended front housing** allows easy access to recessed work pieces
- ❖ **Lightweight** at 1.9Kg for reduced user fatigue
- ❖ **Features constant speed control, soft start speed control and variable speed control** for improved control and safety