

Pressure Cleaners & Accessories









TOUGH MACHINES REAL RESULTS!

Electric Water Blasters for the Budget Conscious

Here at Kerrick we don't muck around, we talk to our customers, listen to what they want and try to find a solution that meets their needs. We understand you want rugged, reliable water blasters that won't break down at prices that won't break the bank!

We've sourced products that can meet your budget needs and our high quality standards. We put them to the test and they did us proud, so proud we're recommending them for commercial and industrial use.

We've been at it since 1937. We know what works. Call 1300 KERRICK and talk to a local!









SPECS ↓	ELITE ROSSO	ECON. EI1511	ROYAL ROSSO
Pressure	120 Bar (1640psi)	100 Bar (1460psi)	210 Bar (3000psi)
Flow	12 lpm	11 lpm	16.6 lpm
Motor	Electric, 2.2kW	Electric, 2.2kW	Electric, 7.5kW
Voltage	Single Phase, 240V 50Hz	Single Phase, 240V 50Hz	Three Phase, 400V 50Hz
Pump Make	-	Interpump	-
Pump Speed	1425 RPM	1450 RPM	1450 RPM
Max Temperature	Cold Water	Cold Water	Cold Water
HPHose Type	3/8 in single wire braid	3/8 in two wire braid	3/8 in single wire braid
HPHose Length	10m	10m	10m
Detergent Tank Size	7.5L	-	4L
Frame Type	Painted Steel, High Impact PVC	Epoxy powder coated steel	Painted Steel, High Impact PVC
Wheels	2	2	2
Weight	44kg	48kg	68kg

SALES

MANUFACTURE



Rugged. Reliable. Efficient.

Powerful Petrol Pressure Cleaners

Grunty machines that give you serious value for money. Commercial and industrial grade - Our cold water petrol water blasters are manufactured to meet the high standards of Australia's professional contracting, building, hire and plumbing industries.

Here at Kerrick we don't muck around, we talk to our customers, listen to what they want and try to find a solution that meets their needs. In addition to our standard product range Kerrick can custom build pressure cleaners with flows of up to 200 litres+ per minute that can be skid, trailer, truck or ute mounted.

We've been at it since 1937. We know what works. Call 1300 KERRICK and talk to a local!

The most popular units in this range:				
SPECS	Hyqua Blitz Cat 2500 psi	Hyqua Blitz Cat 4200 psi	HH3017H Industrial 3000 psi	HH4021 Honda 4000 psi
Pressure	230 Bar (3300psi)	290 Bar (4200psi)	210 Bar (3000psi)	280 Bar (4000psi)
Flow	9.5 lpm	14.8 lpm	17 lpm	21 lpm
Motor	Honda Petrol, 6.5HP	Honda Petrol	Honda Petrol, 13HP	Honda Petrol, 20HP
Pump Make	Cat Pumps	Cat Pumps	Hawk Pumps	Hawk Pumps
Pump Speed	3400 RPM	3400 RPM	1500 RPM	1800 RPM
Max Temperature	Cold Water	Cold Water	Cold Water	Cold Water
HP Hose Type	3/8 in two wire braid	3/8 in two wire braid	3/8 in single wire braid	3/8 in two wire braid
HP Hose Length	15m	15m	10m	10m
Fuel Tank Size	6.1L	6.1L	9L	11L
Frame Type	Aircraft grade aluminium, anti- vibration feet	Aircraft grade aluminum, anti-vibration feet	Zinc plated, roll over	Galvanized, roll over
Wheels	2	2	2	4



Industrial Grade Solutions

European Steam Cleaners

Industrial grade steam cleaners that just melt the dirt away! These Hot water systems provide a quick and easy means of removing sticky and greasy residues without the need for harsh chemicals, however chemical injection can be used for those tougher clean up jobs. Practically designed they're easy to use, easy to maintain, rugged and durable. They also double up as cold water pressure cleaners providing extra value for money!!!

Features: Italian manufacturing, high pressure detergent injection, easy access for maintenance, heating to 100°C+, Italian pumps. Gun and lance provided as standard!

We've been at it since 1937. We know what works. Call 1300 KERRICK.









SPECS ↓	RHINO	НІРРО	JUMBO
Pressure	120 Bar (1750psi)	200 Bar (2910psi)	200 Bar (2910psi)
Flow	11 lpm	15 lpm	21 lpm
Motor	Electric, 2.2kW	Electric, 5.5kW	Electric, 7.3kW
Voltage	Single Phase, 240V 50Hz	Three Phase, 400V 50Hz	Three Phase, 400V 50Hz
Pump Make	Interpump	Interpump	Interpump
Pump Speed	1440 RPM	1450 RPM	1450 RPM
Max Temperature	100 °C	120 °C	100 °C
HPHose Type	3/8 in two wire braid	3/8 in two wire braid	3/8 in two wire braid
HPHose Length	10m	10m	10m
Frame Type	Powder coated / Stainless steel cover	Steel with stainless steel cover	Steel with stainless steel cover
Wheels	4	4	4
Weight	125kg	150kg	170kg
Dimensions	97x60x81	100 x 63 x 85	100 x 63 x 85

SALES -

MANUFACTURE



Get The Full Package.

We sell all the parts & accessories you need.



Pressure Cleaner Nozzles

Spray Nozzles: 0⁰ to 40⁰

Quick Couplings: 0⁰ to 40⁰ and chemical/soaper

Turbo Nozzles: 3000psi to 5000psi

Full Stoneage Range: Banshees, Barracudas,

Spitfires & Warthogs



Guns, Lances & Long Wands

• Guns: Shut Off, Flow Through & Compensating

• Lances: Various lengths and fittings

• Long Wands: 18ft & 24ft telescopic



Hose Reels

- Portable Mini Hose Reel (with pressure gauge)
- Manual Reels
- Hydraulic Reels



High Pressure Hose

- Traditional rubber hose: Comes in single wire or two wire, in a range of diameters and lengths
- Thermoplastic lightweight hose: Comes in a range of diameters and lengths



SALES

MANUFACTURE



Get The Full Package

We sell all the parts & accessories you need

Surface Preparation Nozzles

We carry the popular Barracuda and Spitfire Nozzles that operate in pressures ranging from 15k psi to 40k psi. Our product range is well known in the industry and built to last.

Barracudas are excellent for cleaning difficult and irregular surfaces where an operator can more efficiently maneuver a hand-held tool. These lightweight tools adapt to any high pressure pump and are simple to maintain, making them the most versatile and efficient surface preparation tools in the field.

Spitfires are great for where manual shotgun cleaning is required; the extra lightweight nozzles require little maintenance and are easy to use.

Kerrick has specialists on hand to discuss all your surface preparation needs.

JAMML.
A Few
Samples From
Our Range:





Spitfire SPFR-P8 for operating pressures up to 15k psi



Barracuda BC-K - 2 (2 Nozzles up to 22k psi)



Barracuda BC-H9LF-C (Lower Flows up to 40k psi)

ENGINEERING THE POWER OF WATER	to Tok pai		
Max. Pressure	340 - 1000 bar (5 - 15K psi)	1500 bar (22K psi)	2800 bar (40K psi)
Max. Flow	15 gpm (58 l/min)	15 gpm (57 l/min)	4 gpm (15 l/min)
Inlet Connection	1/2 NPT	9/16 MP	9/16 MP
Nozzles	2 x AP2	2 x AP4	4 x OS7
Diameter	1.7 in. (43mm)	1.8 in. (46mm)	1.8 in. (46mm)
Length	4.8 in. (120mm)	7.8 in. (200mm)	7.8 in. (200mm)
Weight	1.6 lb (0.76kg)	2.6 lb (1.2 kg)	2.6 lb (1.2 kg)

SALES

MANUFACTURE



Get The Full Package

We sell all the parts & accessories you need

Tube, Pipe and Bundle Cleaning Nozzles

We carry the world renowned StoneAge Badger and Banshee Nozzles to support this highly specialized field of pipe, tube and bundle cleaning. Our nozzles operate in pressures ranging from 15k psi to 22k psi and in everything from 0.47" lines to 6" lines.

Badgers nozzles are specialized pipe cleaning tools that negotiate difficult to clean elbows and bends with ease.

Banshees are recognized as an industry standard for unplugging, cleaning, and polishing small tubes, such as those found in heat exchangers and industrial tube bundles.

Kerrick has specialists on hand who can help you choose the correct nozzle for your application, simply call your local branch for more details.

A Few Samples From Our Range:				SOMEON SCOREGE	
STONEAGE ENGINEERING THE POWER OF WATER	2" Badger Pipe Cleaning - 15k psi for 1/4 NPT or BSP Inlets	4" Badger Pipe Cleaning - Operating pressures up to 43.5k psi	Banshee BN9.5 for tubes sized 0.47-0.63 in.	Banshee BN24 for tubes sized 1.1-2.0 in.	
Max. Pressure	1k bar (15K psi)	3000 bar (43.5k psi)	22k psi (1500 bar)	22k psi (1500 bar)	
Max. Flow	15 gpm (57 l/min)	45 l/min (12gpm)	-	-	
Flow Coefficient	0.50 Cv	0.4Cv	0.20 Cv	0.90 Cv	
Rotation Speed	High Speed	100 - 400 rpm (fast fluid)			
Inlet Connections	1/4 NPT, 1/4 BSP	H6 High Pressure Hose	M7, 1/16 NPT, 1/4 LH or 1/4 RH	3/8 NPT, 3/8 BSPP, 9/16 LH or 9/16 RH	

SALES - MANUFACTURE - REPAIR

5 x OS6

2.95 in. (75mm)

3.9 in. (99mm)

0.37 in. (9.5 mm)

2.6 in. (65 mm)

7 x OD3M

1.3 in. (33mm)

2.0 in. (50mm)

Nozzles

Diameter

Length

0.93 in. (24 mm)

5.1 in. (130 mm)



Automated Tube Lancing

AutoBox ABX-500

Introducing the latest technology from StoneAge Waterblast Tools, the AutoBox ABX-500 is a safe and reliable hose handling option for cleaning pipes with rotary jetting tools that is revolutionizing safety in the work place all over the world.

Traditional methods require the operator to hand feed hose while cleaning pipes, which can cause streaking, fatigue and increased safety risk. This portable, air powered tube lancing system can be safely run by a single operator from outside of the blast zone, drastically reducing any chance of injury as a result of hose bursts or couplings failing.

This system is ideal for hands-free pipe cleaning operations where safety is a priority or for the consistent cleaning of pipes where space is limited. Not only does it greatly improve safety but it's more operator friendly, reduces hose wear and is easier to transport than any of its predecessors.




- Smaller, lighter and more portable than a rotary hose device
- Requires a single operator to run
- Passes couplings for continuous operation
- Safely operated from outside the blast zone
- Reduces hose wear

Specifications	
Holding Force	Up to 91 kg
Retract Rate	6 - 9 m/min reverse
Hose size	14 - 45mm OD
Coupling size	Up to 45 mm
Dimensions	483 x 330 x 305 mm
Weight	41 kg

To find out more about this revolutionary new equipment call us today on: 1300 KERRICK









Get The Full Package.

We sell all the parts & accessories you need.

Thermoplastic High Pressure Hose

Kerrick now stocks high pressure performance, flexible and lightweight thermoplastic hose. There has been a need for light weight, robust hose in the market place for many years now and Kerrick has finally cracked the code. Our new range of hose has a thermoplastic elastomer core with double synthetic fibre reinforcing and is sold by the roll.

We carry a range of sewer jetting hoses from our new and improved thermoplastic hose through to the more traditional HP rubber hose, talk to your local branch to find out which type of hose best suits your application.

SPECS L	1/4 Inch 4000 psi Hose (60m)	3/8 Inch 4000 psi Hose (150m)	1/2 Inch 4000 psi Hose (120m)
Hose ID (Nom.)	1/4" (6.4mm)	3/8" (9.5mm)	1/2" (12.7mm)
Hose OD (Nom.)	0.500" (12.7mm)	0.67" (17mm)	0.880" (22.4mm)
Working Pressure	4,000 psi (275 bar)	4000 psi (280 bar)	4,000 psi (275 bar)
Min. Burst Pressure	10,000 psi (840 bar)	12000 psi (840 bar)	10,000 psi (840 bar)
Min. Bend Radius	1.6" (40mm)	8" (75mm)	3" (75mm)
Length	60m	150m	120m
SPECS ↓	3/4 Inch 2500 psi Hose (120m)	3/4 Inch 3000 psi Hose (150m)	1 Inch 3000 psi Hose (150m)
Hose ID (Nom.)	3/4" (19mm)	3/4" (19mm)	1" (25.4mm)
Hose OD (Nom.)	1.250" (31.8mm)	1.250" (31.8mm)	1.525" (38.7mm)
Working Pressure	2,500 psi (170 bar)	3,000 psi (210 bar)	3,000 psi (210 bar)
Min. Burst Pressure	7,500 psi (525 bar)	7,500 psi (525 bar)	7,500 psi (525 bar)
Min. Bend Radius	5" (125mm)	5" (125mm)	6.4" (160mm)

SALES

MANUFACTURE