

# TOKU

## Light & Handy Die Grinder - Used with stone or burr for general maintenance job



Rear exhaust

**MG-7206B**



Front exhaust

**MG-7236B**

- High speed, low vibration
- Compact, light & handy
- Ideal for grinding and deburring
- 6 mm collet (Standard)  
Optional 1/4" or 3 mm collet on request



Front exhaust

**MG-7204B**



Front exhaust

**MG-20**

Specifications: Air Pressure 6kg/cm<sup>2</sup>

Code	Model	Collet Size	Wheel Size	Net Weight	OA Length	Free Speed	Avg. Air Cons	Air Inlet	Hose Size
		(mm)	(mm)	(kg)	(mm)	(rpm)	(m <sup>3</sup> /min)	(pt)	(in)
<b>ALA 0048</b>	MG-7206B	6 (3 & 1/4" Optional)	25	0.6	146	20,000	0.28	1/4	3/8
<b>ALA 0049</b>	MG-20	6 (3 & 1/4" Optional)	25	0.6	139	20,000	0.28	1/4	3/8
<b>ALA 0050</b>	MG-7236B	6 (3 & 1/4" Optional)	25	0.4	123	15,000	0.23	1/4	3/8
<b>ALA 0051</b>	MG-7204B	6 (3 & 1/4" Optional)	25	0.4	120	25,000	0.23	1/4	3/8

## Die Grinder & Straight Grinder - Industrial duty

Straight Grinders are Industrial Heavy Duty for general Grinding, Sanding and Wire Brushing Applications



For more option on the Carbide Burs, please refer to **PRO CUT Carbide Burs**



For more options on the wire brushes, please refer to **Industrial Wire Brushes**

**ATD-6752 Adjustable Air Regulator**



To regulate air flow and control Air Tool speed & power.



6mm collet Die Grinder

**TG-25ZII**



6mm collet Die Grinder

Motor cap Ø: 35mm

**TG-38Z**



3" Straight Grinder

**TSG-3F**



6mm collet Die Grinder

**TSG-3C**



5" Straight Grinder, Wire Brushing

**TSG-5S**



6" Straight Grinder, Wire Brushing

**TSG-6S**

Code	Model	Wheel Size	Collet Size	Max Cut Speed	Net Weight	Overall Length	Free Speed	Avg. Air Consumption	Air Inlet	Hose Size	Power
		(mm)	(mm)	(m/min)	(kg)	(mm)	(rpm)	(m <sup>3</sup> /min)	(pt)	(in)	(HP)
<b>ALA 0052</b>	TG-25ZII	25	6	-	0.6	150	18,000	0.23	1/4	3/8	0.4
<b>ALA 0053</b>	TG-38Z	25	6	-	0.7	178	23,000	0.23	1/4	3/8	0.4
<b>ALA 0054</b>	TSG-3C	38	6	-	1.7	330	12,700	0.50	1/4	1/2	0.7
<b>ALA 0055</b>	TSG-3F	75 x 13 x 9.5	-	3,000	1.6	305	12,700	0.50	1/4	1/2	0.7
<b>ALA 0056</b>	TSG-5S	125 x 19 x 12.7	-	3,000	3.3	400	7,600	1.20	3/8	1/2	1.4
<b>ALA 0057</b>	TSG-6S	150 x 25 x 15.9	-	3,000	4.5	430	6,300	1.20	3/8	1/2	2.1