

- ▲ Greasing Equipment
- ▲ Fuel Transfer
- ▲ Hose Reels
- ▲ Oil Transfer
- ▲ Spill Containment





## EL SERIES

Alemlube's EL Series of lubrication equipment, as released in February 2010, offers excellent value for money.

Not everyone needs or can justify a Rolls Royce and this is where the EL Series comes into its own. Ideal for seasonal or intermittent use or the weekend warrior each and every EL Series product has undergone rigorous field testing before being added to the Alemlube product range.

Sold and promoted under the Alemlube brand, but clearly different due to its colour (grey) and subtly different packaging and labelling, Alemlube's EL Series provides end users with confidence and peace of mind whilst at the same time enabling you, the Distributor, to have one consolidated source of supply for all of your lubrication equipment products.

G10010N

## 450g Trigger Action Grease Gun

- ▲ Develops grease pressures of up to 4,000psi
- ▲ 500g capacity when using bulk grease
- ▲ Three way loading
- ▲ Unique follower cup design makes the gun suitable for use with both 450g cartridges and bulk grease – without needing to change the orientation of the follower cup
- ▲ Includes a 300mm long grease gun flex and heavy duty four jaw coupler



GREASING

G10020N

## 450g Lever Action Grease Gun

- ▲ Develops grease pressures of up to 8,000psi
- ▲ 500g capacity when using bulk grease
- ▲ Three way loading
- ▲ Unique follower cup design makes the gun suitable for use with both 450g cartridges and bulk grease – without needing to change the orientation of the follower cup
- ▲ Includes a 150mm long grease rigid extension and heavy duty four jaw coupler



GREASING

G10030

## 450g Air Operated Grease Gun

- ▲ Develops grease pressures of up to 6,000psi
- ▲ Continuous grease flow ensures effortless greasing
- ▲ Three way loading
- ▲ Exclusive air piston design ensures consistent priming
- ▲ 450g cartridge capacity
- ▲ Includes a 300mm long grease gun flex and four jaw coupler



GREASING

G10040

## 450g 18V Cordless Grease Gun

- ▲ Develops grease pressures of up to 10,000psi
- ▲ Delivery rates of up to 80 g/min
- ▲ Can be used with up to four 450g cartridges before recharging or battery changeover is required
- ▲ 75 minutes battery recharge time
- ▲ Includes a 106cm flexible extension
- ▲ **Also available G10044 suits 400g cartridges**



GREASING

G10050N

## 85g Mini Pistol Grease Gun

- ▲ Develops grease pressures of up to 3,500psi
- ▲ Zinc die-cast head construction
- ▲ Suits bulk grease and 85g grease cartridges
- ▲ Two way loading
- ▲ Heavy duty four jaw coupler



GREASING

G10060N

## Coupler



- ▲ 4 jaw coupler for standard hydraulic grease nipples

G10070N

## 30cm Grease Gun Flex



- ▲ Industrial quality high flexibility grease gun flex

G10080N

## 40cm Grease Gun Flex



- ▲ Industrial quality high flexibility grease gun flex

F20010

## 12V Diesel Fuel Drum Pump

- ▲ Flow rates of up to 30 L/min
- ▲ Innovative vertically installed centrifugal pump
- ▲ Double insulated motor body
- ▲ In built on/off switch
- ▲ Equipped with a 12V DC motor and supplied with suction and delivery hoses, a manual nozzle, 3m of battery cable with clamps and an inlet filter
- ▲ Compact, portable, versatile and weighs only 4.5kg



FUEL  
TRANSFER

F20020

## 12V Refuelling Kit

- ▲ Flow rates of up to 38 L/min
- ▲ Self priming rotary vane pump
- ▲ Suction capacity of up to 2m
- ▲ Duty cycle of 30 minutes on, 30 minutes off
- ▲ Equipped with a 12V DC motor and supplied with suction and delivery hoses, battery cable with clamps, inlet filter and a manual plastic nozzle
- ▲ Compact, completely portable, simple installation and easy to use



FUEL  
TRANSFER



F20050

## Rotary Drum Pump

- ▲ Aluminium alloy body & long lasting neoprene seal
- ▲ Flow rates of up to 28 L/min
- ▲ Suitable for transferring petrol, diesel, kerosene, oil and hydraulic fluid
- ▲ Suction distance of up to 1.5m, lift capability of 4.8m
- ▲ For use with 205L drums



FUEL  
TRANSFER

F20030

## Automatic Shut Off Fuel Nozzle

- ▲ Compact, lightweight and easy to use
- ▲ Flow rates of up to 80 L/min
- ▲ Minimum pressure loss facilitates maximum flow rates
- ▲ Supplied complete with an integral swivel
- ▲ Can be locked in the on position
- ▲ Suitable for applications involving a pump only
- ▲ F20030U also available for use with unleaded fuel



FUEL  
TRANSFER

F20040

## Manual Fuel Nozzle

- ▲ Strong aluminium construction
- ▲ Flow rates of up to 80 L/min
- ▲ Equipped with an integrated swivel connector
- ▲ Hammer-free valve facilitates efficient fuel delivery
- ▲ Suitable for use with any fuel transfer system even gravity applications
- ▲ Features include lever protection and a removable trigger lock



FUEL  
TRANSFER

WO50010

## Oil Suction Gun

- ▲ Metal construction and 500mL capacity
- ▲ Ideal for the draining or topping up of gear boxes, differentials, transmissions and master break cylinders
- ▲ Handles oils up to SAE 90
- ▲ 290mm long flexible extension
- ▲ Cup packing type seal
- ▲ Toughened powder coated finish and knurled non-slip barrel for ease of use.



WASTE  
OIL



HR40010

## Air Hose Reel

- ▲ Supplied with 15m x fitted 10mm ID hose
- ▲ Impact resistant polypropylene construction
- ▲ Maximum working pressure of up to 300psi
- ▲ Automatic and positive latching mechanism
- ▲ 3/8" inlet & outlet connections
- ▲ Inclusive of an integral wall/ceiling mounting bracket and 0.9m lead in hose
- ▲ Ideal for use with drills, impact wrenches, angle grinders, ratchets & tyre gauges



AIR  
DELIVERY

HR40020

## Air & Water Hose Reel

- ▲ Supplied with 15m x fitted 12mm ID hose
- ▲ Made from high quality impact resistant polypropylene
- ▲ Maximum working pressure of up to 300psi
- ▲ 1/2" inlet & outlet connections
- ▲ Automatic spring rewind retrieves, stores & protects air/water hose
- ▲ Inclusive of an integral wall/ceiling mounting bracket and 0.9m lead in hose
- ▲ Ideal for use with drills, impact wrenches, angle grinders, ratchets & tyre gauges



AIR & WATER  
DELIVERY

## SC60010N

### 2 Drum Spill Container

- ▲ Designed for static spill containment for up to 2 x 205L drums
- ▲ Manufactured from high strength polyethylene that will not rust or corrode
- ▲ 220L capacity
- ▲ Compatible with most forklifts and pallet trucks
- ▲ Removable grid deck for ease of cleaning
- ▲ Helps to create an OH&S compliant workplace environment
- ▲ Dimensions of 1320 x 670 x 420mm
- ▲ Multiple units can connect to create customised drum storage and spill containment platforms. No additional parts required



SPILL  
CONTAINMENT

## SC60020N

### 4 Drum Spill Container

- ▲ Designed for static spill containment for up to 4 x 205L drums
- ▲ Manufactured from high strength polyethylene that will not rust or corrode
- ▲ 440L capacity
- ▲ Compatible with most forklifts and pallet trucks
- ▲ Removable grid deck for ease of cleaning
- ▲ Helps to create an OH&S compliant workplace environment
- ▲ Dimensions of 1320 x 1340 x 420mm
- ▲ Multiple units can connect to create customised drum storage and spill containment platforms. No additional parts required



SPILL  
CONTAINMENT

O30010

## 20L Gear Oil Drum Pump

- ▲ Now capable of delivering up to 80mL per stroke
- ▲ Ideal pump for the transfer of engine gear, diff and hydraulic oils in busy vehicle servicing workshops
- ▲ Drainback nozzle holster ensures that excess oil ends up back in the drum
- ▲ Now incorporates a filter in the drain back holster to protect against foreign particle contamination
- ▲ UV stabilised long life hose ensures a long service life
- ▲ Delivers lubricant on the down stroke



OIL  
TRANSFER



### PACKAGING DESIGN

New style packaging has been designed to provide a unique identity for the Alemlube EL Series range of products.

The colours are consistent with the Alemlube corporate colourway, yet the new design allows the EL Series to stand tall with its own identity and market presence.