



PRODUCT INFORMATION

June 2015

8338

Foot Operated Grease Bucket Pump

The Alemlube 8338 foot operated grease bucket pump with its 8kg capacity allows the user to spend more time greasing valuable plant and equipment and less time refilling or changing over traditional grease gun cartridges.

Manufactured with true industrial strength components, the 8338 foot operated pumping process guarantees consistent pressure meaning no more stressed hands and arms when greasing multiple joints and bearings. Simply lift the foot treadle to return residual pressure back to the canister.

The patented pressure return valve in conjunction with the unique Alemlube 14512 quick release grease gun coupler supplied as standard, helps the user to save grease, eliminate dribble and waste and effectively extends grease coupler and nipple life.

The easy lock-on mechanism of the coupler allows for total hands free operation and the easy clip-off, regardless of pressure built up in the line, means that the 8338 is extremely OH&S friendly and is ideal for greasing fittings in difficult to reach and unsafe places and furthermore allows the user to conduct greasing safely from a distance with the 2.8m hydraulic delivery hose.

Complete with a comfortable fold away carry handle for portability, canister lid to help keep contaminants out of your grease and rubber foot mounts ensuring pumping stability, the 8338 foot operated grease bucket pump available from Alemlube is the ideal greasing system for fast and efficient lubrication in the field.



PRODUCT SPECIFICATIONS, FEATURES AND BENEFITS

Grease pressure of up to 10,000psi (690 bar)

Delivery rates of up to 2.7cc per stroke

Grease canister capacity of 8kg

User friendly foot operated pump activation

Patented pressure return valve

Alemlube 14512 quick release grease gun coupler supplied as standard

Coupler pressure rating of 10,000psi (690 bar)

1/8" BSP (f) coupler thread

2.8m x 1/4" ID 2 wire hydraulic delivery hose

Delivery hose burst rating of 23,200psi (1,600 bar)

Dimensions of 470mm (L) x 260mm (W) x 420mm (H)

Dry weight of 10kg

ORDERING INFORMATION: 8338 Foot Operated Grease Bucket Pump

