

TOKU 



# CONSTRUCTION & INDUSTRIAL TOOLS

Ver 2.02

**TOKU PNEUMATIC CO., LTD.**  
[www.toku-net.co.jp/en](http://www.toku-net.co.jp/en)

# CHIPPING HAMMERS

## AA FEATURES

- Compact and lightweight design superior for precise job operation
- Open handle enables comfortable grip even with safety gloves
- High BPM performance for most effective productivity

NEW MODEL

AA-OS



## THA FEATURES

- Available in 1" to 4" stroke for best selection in various applications
- Durable handle design technology based on 30 years of actual job site experience
- Unique ring valve design for optimum operation in tough applications or dirty environments
- Available chuck size - .680 round or .580 hex

THA-1B



THA-2B



THA-3B



THA-4B



## TCH FEATURES

- Four bolt handle for excellent durability
- Available in 2" to 4" stroke for best selection in various applications
- Available chuck size - .680 round or .580 hex

TCH-2



TCH-3



TCH-4



## LONG REACH FLOOR SCALER

### THA-LR FEATURES

- Ideal for surface cleaning operation such as removing tiles, paint, rubber coating, grout, etc. Also available for roughening concrete/masonry.
- Powerful design hammer body, yet high BPM's for effective job operation



NEW MODEL

THA-2B-LR

## SPECIFICATION

MODEL	CHUCK SIZE inch	STROKE inch (mm)	BORE inch (mm)	IMPACT RATE B.P.M.	WEIGHT lb (kg)	LENGTH inch (mm)	AIR CONSUMPTION CFM (m <sup>3</sup> /min)	AIR INLET inch	HOSE SIZE inch (mm)
AA-OS	.680 Round or .580 Hex	1-3/4(45)	7/8(22.2)	3,000~3,200	8(3.6)	12-3/4(320)	23(0.65)	3/8 NPT	1/4(6.3)
THA-1B	.680 Round or .580 Hex	1(25.4)	1-1/8(28.54)	2,500	13(5.9)	15-5/16(388)	28(0.79)	3/8NPT	1/2(12.7)
THA-2B	.680 Round or .580 Hex	2(51)	1-1/8(28.54)	2,300	14(6.2)	16-1/4(413)	30(0.85)	3/8NPT	1/2(12.7)
THA-3B	.680 Round or .580 Hex	2-1/2(64)	1-1/8(28.54)	2,200	15(6.8)	17-3/4(450)	32(0.9)	3/8NPT	1/2(12.7)
THA-4B	.680 Round or .580 Hex	4(102)	1-1/8(28.54)	1,800	15.5(7)	19(480)	33(0.95)	3/8NPT	1/2(12.7)
THA-2B-LR	.680 Round or .580 Hex	2(51)	1-1/8(28.54)	2,300	20(9)	58(1,470)	30(0.85)	1/2 NPT	1/2(12.7)
TCH-2	.680 Round or .580 Hex	2(50.8)	1-1/8(28.54)	2,600~2,800	18(8.1)	14-3/4(374.65)	30(0.85)	7/8-24 NPT-Female	1/4(6.3)
TCH-3	.680 Round or .580 Hex	2-1/2(63.5)	1-1/8(28.54)	2,000~2,200	19(8.55)	16(406.4)	31.5(0.89)	7/8-24 NPT-Female	1/4(6.3)
TCH-4	.680 Round or .580 Hex	4(101.6)	1-1/8(28.54)	1,600~1,800	20(9)	17(431.79)	33(0.95)	7/8-24 NPT-Female	1/4(6.3)

Dynamic pressure: 90 PSI (0.6MPa) for all products